

Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (http://phoenixcontact.com/download)

Housing cover, for connection on one side



Illustration shows a fully mounted version of the electronic housing

Product Features

- ▼ Tool-free mounting
- Functional and industry-oriented housing technology
- ☑ Date of manufacture and material and part identification embossed on the housing (recyclability)
- ☐ Practical and easy-to-wire conductor connection using extra finely stranded sturdy screw terminal blocks up to 2.5 mm²
- Fast snap-on mounting on symmetrical DIN rails according to EN 60715
- Optimum accommodation of electronic components with graded pitches with a design width of 22.5 mm, 45 mm, 67.5 mm, and 90 mm
- Shock and contamination-proof accommodation of electronic components (IP40 housing, IP20 terminal blocks)



Key commercial data

Packing unit	1 pc
Minimum order quantity	10 pc
GTIN	4 017918 131968
Weight per Piece (excluding packing)	17.74 GRM
Custom tariff number	85369010
Country of origin	Germany

Technical data

General

Housing type	Component housing
Color	green



Technical data

Ambient conditions

Ambient temperature (operation)	80 °C
Dimensions	
Constructional height	17.5 mm
Width	67.5 mm

Technical data

Inflammability class according to UL 94	V0
Number of positions	26

Classifications

eCl@ss

eCl@ss 4.0	27180401
eCl@ss 4.1	27180401
eCl@ss 5.0	27180506
eCl@ss 5.1	27180506
eCl@ss 6.0	27180802
eCl@ss 7.0	27182702
eCl@ss 8.0	27182702

ETIM

ETIM 2.0	EC001031
ETIM 3.0	EC001031
ETIM 4.0	EC001031
ETIM 5.0	EC000886

UNSPSC

UNSPSC 6.01	31261501
UNSPSC 7.0901	31261501
UNSPSC 11	31261501
UNSPSC 12.01	31261501
UNSPSC 13.2	31261501


Approvals

Approvals




Approvals UL Recognized Ex Approvals Approvals submitted Approval details UL Recognized

Drawings











valid for PCB 13






valid for PCB 14






Component mounting side, if the double-level upper part is used






valid for PCB 1; 2; 3; 4; 5 und 6, see explosion drawing





valid for PCB 7; 8; 11 and 12, see explosion drawing





valid for PCB 9, see explosion drawing

Phoenix Contact 2014 @ - all rights reserved http://www.phoenixcontact.com