

Part Number: 5403FE



Security & Sound, #20-5c, BC, Shielded, CMR

# **Product Description**

Security & Sound Cable, Riser-CMR, 5-20 AWG stranded bare copper conductors with polyolefin insulation, Beldfoil® shield and PVC jacket with ripcord

# **Technical Specifications**

## **Physical Characteristics (Overall)**

Condu	Conductor			
AWG	Stranding	Material	No	. of Conductors
20	7x28	BC - Bare Coppe	er 5	
Conductor Count: 5				
Condu	Conductor Size:		20 AWG	

#### Insulation

Material	Nominal Wall Thickness
PP - Polypropylene	0.008 in

### Color Chart



## **Outer Shield Material**

Type	Material	Material Trade Name	Coverage [%]	Drainwire Material	Drainwire AWG	Drainwire Construction n x D
Tape	Aluminum/Polyester	Beldfoil®	100 %	TC - Tinned Copper	24	Solid

## Outer Jacket Material

Material	Nominal Diameter	Nominal Wall Thickness	Ripcord
PVC - Polyvinyl Chloride	0.172 in	0.017 in	Yes

# **Construction and Dimensions**

Print Legend: NEW GENERATION(R) BY BELDEN-M 5403FE CMR 75C 5C20 SHIELDED (UL) E108998 OR C(UL) CMG (2 FT., 7 DIGIT SEQUENTIAL) FEET

## **Electrical Characteristics**

## Conductor DCR

Nominal Conductor DCR	Nominal Outer Shield DCR
10.2 Ohm/1000ft	10.9 Ohm/1000ft

## Capacitance

Nom. Capacitance Conductor to Conduct	Nom. Capacitance Conductor to Other Conductor to Shield
26 pF/ft	46.75 pF/ft
Shielding:	Foil(s) or Copper Tape(s)

### Current

Max. Recommended Current [A]

#### Voltage



### **Temperature Range**

UL Temp Rating:	75°C
Operating Temp Range:	-20°C To +75°C

### **Mechanical Characteristics**

Bulk Cable Weight:	26 lbs/1000ft
Max Recommended Pulling Tension:	72.1 lbs
Min Bend Radius/Minor Axis:	1.75 in

### **Standards**

NEC Articles:	800
NEC/(UL) Specification:	CMR
CEC/C(UL) Specification:	CMG

## **Applicable Environmental and Other Programs**

EU Directive 2000/53/EC (ELV):	Yes
EU Directive 2003/96/EC (BFR):	Yes
EU Directive 2011/65/EU (ROHS II):	Yes
EU Directive 2012/19/EU (WEEE):	Yes
EU Directive Compliance:	EU Directive 2003/11/EC (BFR)
EU CE Mark:	Yes
EU RoHS Compliance Date (yyyy-mm-dd):	2005-04-01
CA Prop 65 (CJ for Wire & Cable):	Yes
MII Order #39 (China RoHS):	Yes

# Flammability, LS0H, Toxicity Testing

UL Flammability:	UL1666 Riser
CSA Flammability:	FT4
UL voltage rating:	300 V RMS

# Plenum/Non-Plenum

Plenum (Y/N):	No
Plenum Number:	6403FE

## **Part Number**

### Variants

Item #	Color	Footnote
5403FE 0081000	Gray	С
5403FE 008U1000	Gray	
Footnoto:		

Footnote: C - CRATE REEL PUT-UP

### © 2018 Belden, Inc

# All Rights Reserved.

Although Belden makes every reasonable effort to ensure their accuracy at the time of this publication, information and specifications described here in are subject to error or omission and to change without notice, and the listing of such information and specifications does not ensure product availability.

Belden provides the information and specifications herein on an "ASIS" basis, with no representations or warranties, whether express, statutory or implied. In no event will Belden be liable for any damages (including consequential, indirect, incidental, special, punitive, or exemplary damages) whatsoever, even if Belden has been advised of the possibility of such damages, whether in an action under contract, negligence or any other theory, arising out of or in connection with the use, or inability to use, the information or specifications described herein.

All sales of Belden products are subject to Belden's standard terms and conditions of sale.

Belden believes this product to be in compliance with all applicable environmental programs as listed in the data sheet. The information provided is correct to the best of Belden's knowledge, information and belief at the date of its publication. This information is designed only as a general guide for the safe handling, storage, and any other operation of the product itself or the one that it becomes a part of. The Product Disclosure is not to be considered a warranty or quality specification. Regulatory information is for guidance purposes only. Product users are responsible for determining the applicability of legislation and regulations based on their individual usage of the product.