



| | |
|---|---|
| D | |
| C | <p>Wire _____ Tinned copper</p> <p>Gauge _____ AWG 28/7 0,089 mm²</p> <p>Voltage rating _____ 300 Vr.m.s</p> <p>Current rating _____ 2,1A at 25°C</p> <p>Capacity unbalanced _____ 45,9 pF/m at 1 MHz</p> <p>Impedance unbalanced _____ 105 Ω</p> <p>Propagation delay _____ 4,9 ns/m nominal</p> <p>Insulation material _____ PVC</p> <p>Temperature rating _____ -20°C (operating) _____ -30°C (static) to +105°C</p> <p>Flammability rating _____ Flame retardant VW1</p> <p>Insulation resistance _____ 100 MΩ/km</p> <p>Approval _____ UL AWM style 2651</p> |
| B | |
| A | |

| | |
|----------------|--------------------|
| 09 18 020 7004 | 100 m (328 feet) |
| 09 18 020 7001 | 30,48 m (100 feet) |
| Part number | Length per reel |

| | | | | | | | | |
|---------|----------|----|---------|----------|-------------------------------|---|-------------------------------|-------------------------------|
| | | | | Det. | Name |  All Dim. in mm Orig. Size DIN A 4 | SEK 18 flat cable 20 poles | Maßstab/ Scale 10:1 |
| | | | Detail. | 20/10/05 | JMDR | | | |
| | | | Insp. | | | | | |
| EC01360 | 19/02/10 | SC | Stand. | | | | | |
| | | | | | |  | TB 09 18 020 700X | Blatt/ Page 1 / 1 |
| | | | | | HARTING EURL F-95972 Paris | | | |
| | | | | | | | | |
| | | | Mod. | Det. | Name | | | |